



Technical requirements:

- 1、 Please use our specified grease;
- 2、 Dimensions with \* in the drawing are installation reference dimensions, please follow this installation dimension requirement;
- 3、 Please use the delivery specification drawing to confirm the details of the dimensions.

型号/MODEL	U	T	W	型号 Model	速比 Reduction ratio	输入2000r/min时的 额定转矩 Rated torque at 2000r/min input	起动停止时的 容许峰值转矩 Permissible peak torque at start and stop	平均负载转矩的 容许最大值 Permissible maximum value for average load torque	瞬间容许最大转矩 Permissible maximum momentary torque	容许最高 输入转速 (脂润滑) Permissible maximum input rotational speed(Grease)	容许平均 输入转速 (脂润滑) Permissible average input rotational speed(Grease)	背隙 Backlash	重量 Weight	设计寿命 Desian life
Wave generator-A φ8	φ8H7	9.4 <sup>+0.1</sup>	3P9/JS9			Nm	Nm	Nm	Nm	r/min	r/min	Arc Sec	Kg	Hour
Wave generator-A φ15	φ15H7													
HSD-17-XX-U-I	Harmonic Drive Model 17													
Homwing	Shenzhen homwing technology co.,ltd	17		50	11	23	18	48	7300	3500	≤20	HSD-I:0.42	9000	
				80	14	29	21	54					10000	
				100	16	37	27	71					10000	