



Technical requirements:

- 1、 Please use our specified grease;
- 2、 Dimensions with * in the drawing are installation reference dimensions, please follow this installation dimension requirement;
- 3、 Please use the delivery specification drawing to confirm the details of the dimensions.

型号/MODEL	U	T	W	型号 Model	速比 Reduction ratio	输入2000r/min时的 额定转矩 Rated torque at 2000r/min input	启动停止时的 容许峰值转矩 Permissible peak torque at start and stop	平均负载转矩的 容许最大值 Permissible maximum value for average load torque	瞬间容许最大转矩 Permissible maximum momentary torque	容许最高 输入转速 (脂润滑) Permissible maximum input rotational speed(Grease)	容许平均 输入转速 (脂润滑) Permissible average input rotational speed(Grease)	背隙 Backlash	重量 Weight	设计寿命 Desian life
Wave generator-A φ8	φ8H7	9.4 ^{+0.1}	3P9/JS9			Nm	Nm	Nm	Nm	r/min	r/min	Arc Sec	Kg	Hour
Wave generator-A φ20	φ20H7													
HSD-20-XX-U-I	Harmonic Drive Model 20													
Homwing	Shenzhen homwing technology co.,ltd			20	50	17	39	24	69	6500	3500	≤20	HSD-I:0.54	9000
					80	23	49	28	78					10000
					100	28	57	34	95					10000