



Technical requirements:

- 1、 Please use our specified grease;
- 2、 Dimensions with \* in the drawing are installation reference dimensions, please follow this installation dimension requirement;
- 3、 Please use the delivery specification drawing to confirm the details of the dimensions.

HST-17-XX-U-III	Harmonic Drive Model 17	型号 Model	速比 Reduction ratio	输入2000r/min时的 额定转矩 Rated torque at 2000r/min input		起动停止时的 容许峰值转矩 Permissible peak torque at start and stop		平均负载转矩的 容许最大值 Permissible maximum value for average load torque		瞬间容许最大转矩 Permissible maximum momentary torque		容许最高 输入转速 (脂润滑) Permissible maximum input rotational speed(Grease)	容许平均 输入转速 (脂润滑) Permissible average input rotational speed(Grease)	背隙 Backlash	重量 weight	设计寿命 Desian life
				Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec	kg	Hour
Homwing	Shenzhen homwing technology co.,ltd	17	50	16	1.6	34	3.5	26	2.6	70	7.1	7300	3500	≤20	HST-III:0.99	10000
			80	22	2.2	43	4.4	27	2.7	87	8.9					15000
			100	24	2.4	54	5.5	39	4.0	110	11					15000
			120	24	2.4	54	5.5	39	4.0	86	8.8					15000