



Technical requirements:

- 1、 Please use our specified grease;
- 2、 Dimensions with * in the drawing are installation reference dimensions, please follow this installation dimension require ment;
- 3、 Please use the delivery specification drawing to confirm the details of the dimensions.

| 型号 Model | 速比 Reduction ratio | 输入2000r/min时的 额定转矩 Rated torque at 2000r/min input | | 起动停止时的 容许峰值转矩 Permissible peak torque at start and stop | | 平均负载转矩的 容许最大值 Permissible maximum value for average load torque | | 瞬间容许最大转矩 Permissible maximum momentary torque | | 容许最高 输入转速 (脂润滑) Permissible maximum input rotational speed(Grease) | 容许平均 输入转速 (脂润滑) Permissible average input rotational speed(Grease) | 背隙 Backlash | 重量 weight | 设计寿命 Desian life | |
|-----------------|-------------------------------------|---|------|--|------|---|------|---|------|--|--|----------------|--------------|---------------------|-------|
| | | Nm | kgfm | Nm | kgfm | Nm | kgfm | Nm | kgfm | r/min | r/min | Arc Sec | kg | Hour | |
| HST-20-XX-U-III | 20 | 50 | 25 | 2.5 | 56 | 5.7 | 34 | 3.5 | 98 | 10 | 6500 | 3500 | ≤20 | HST-III:1.32 | 10000 |
| | | 80 | 34 | 3.5 | 74 | 7.5 | 47 | 4.8 | 127 | 13 | | | | | 15000 |
| Homwing | Shenzhen homwing technology co.,ltd | 100 | 40 | 4.1 | 82 | 8.4 | 49 | 5.0 | 147 | 15 | | | | | 15000 |
| | | 120 | 40 | 4.1 | 87 | 8.9 | 49 | 5.0 | 147 | 15 | | | | | 15000 |
| | | 160 | 40 | 4.1 | 92 | 9.4 | 49 | 5.0 | 147 | 15 | | | | | 15000 |