



Technical requirements:

- 1、 Please use our specified grease;
- 2、 Dimensions with * in the drawing are installation reference dimensions, please follow this installation dimension requirement;
- 3、 Please use the delivery specification drawing to confirm the details of the dimensions.

HST-40-XX-U-IV	Harmonic Drive Model 40	型号 Model	速比 Reduction ratio	输入2000r/min时的 额定转矩 Rated torque at 2000r/min input		启动停止时的 容许峰值转矩 Permissible peak torque at start and stop		平均负载转矩的 容许最大值 Permissible maximum value for average load torque		瞬间容许最大转矩 Permissible maximum momentary torque		容许最高 输入转速 (脂润滑) Permissible maximum input rotational speed(Grease)	容许平均 输入转速 (脂润滑) Permissible average input rotational speed(Grease)	背隙 Backlash	重量 weight	设计寿命 Desian life
				Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec	kg	Hour
Homwing	Shenzhen homwing technology co.	ltd 40	50	137	14	402	41	196	20	686	70	4000	3000	≤20	HST-IV:7.00	10000
			80	206	21	519	53	284	29	980	100					15000
			100	265	27	568	58	372	38	1080	110					15000
			120	294	30	617	63	451	46	1180	120					15000